



HYBRID INVERTER

High Frequency MPPT Hybrid Solar Inverter

DP Prime 6KW
DP Max 4KW



DELTAPOWER
GREEN, CLEAN, SMART

SOLAR INVERTER MODEL & SPECIFICATION

FEATURES

- A combination of inverter, solar charger and battery charger.
- Powerful bypass function with uninterrupted power supply function.
- Configurable AC/Solar input priority via LCD setting.
- Compatible with mains voltage or generator power.
- Overload, short circuit, over discharge protection.
- Status indication with RGB lights.
- Touch screen control module with various communications.
- Self-consumption and Feed-in to the grid.
- Compatible with AGM/Sealed, Gel, Flooded, Lithium batteries and a User Mode for custom inputs to work with virtually all battery types.
- MPPT solar charge controller to maximize and regulate DC power from the solar array to charge the battery bank.
- Programmable multiple operation modes: Grid-tie, off-grid and grid-tie with backup.



DATASHEET	4KW	6KW
Max. PV Array Power	5000W	6500W
Rated Output Power	4000W	6000W
Maximum PV Array Open Circuit Voltage	500VDC	500VDC
MPPT Range @ Operating Voltage	60Vdc-450Vdc	
MPPT Tracker Number	1	
GRID-TIE OPERATION		
GRID OUTPUT (AC)		
Nominal Output Voltage	220/230/240 VAC	
Output Voltage Range	184 - 264.5 VAC or 195.5 - 253 VAC (Selectable)	
Nominal Output Current	14.5A	26.1A
Power Factor	> 0.99	
EFFICIENCY		
Maximum Conversion Efficiency (DC/AC)	95%	95%
OFF-GRID, HYBRID OPERATION		
GRID INPUT		
Acceptable Input Voltage Range	90 - 280 VAC or 170 - 280 VAC	
Frequency Range	50 Hz/60 Hz (Auto sensing)	
Maximum AC Input Current	40A	40A
BATTERY MODE OUTPUT (AC)		
Nominal Output Voltage	220/230/240 VAC	
Output Waveform	Pure sine wave	
Efficiency (DC to AC)	93%	
BATTERY & CHARGER		
Nominal DC Voltage	24Vdc	48Vdc
Maximum Solar Charge Current	120 A	120 A
Maximum AC Charge Current	100 A	100 A
Maximum Charge Current	120 A	
GENERAL		
PHYSICAL		
Dimension, D x W x H (mm)	128*300*440	
Net Weight (kgs)	8.7	10.6
INTERFACE		
Communication Ports	USB/RS232/RS485/WIFI	
ENVIRONMENT		
Humidity	0 ~ 90% RH (Non-condensing)	
Operating Temperature	-10°C to 50°C	

Product specifications are subject to change without further notice.

