



# SDT G3 Series

## Three Phase / 2 MPPTs

### 8-30kW



**GOODWE**  
YOUR SOLAR ENGINE

## SOLAR INVERTER MODEL & SPECIFICATION

### FEATURES

The GoodWe SDT G3 Series, with a power range of 8-30 kW, is specifically engineered to cater to the energy needs of three-phase residential and small commercial projects. The inverter boasts an impressive 150% DC oversizing and 110% AC overloading capabilities, allowing for maximum performance and output even in challenging environments. In addition, the SDT G3 Series inverter's lightweight and easy-to-install design offers exceptional convenience for operators and installers alike.



24/7 load consumption monitoring



Elegant and compact design



Max. 22A DC input current per string



Optional Type II SPD on both AC and DC sides



**Smart Control & Monitoring**

- 24/7 load consumption monitoring
- Export power limit



**Friendly & Thoughtful Design**

- Fanless cooling for quiet operation<sup>2</sup>
- Elegant and compact design



**Superb Safety & Reliability**

- Optional AFCI<sup>1</sup>
- IP66 ingress protection
- Optional Type II SPD on both AC and DC sides<sup>1</sup>



**Flexible & Adaptable Applications**

- Up to 150% DC input oversizing & 110% AC output overloading
- Max. 22A DC input current per string
- Optional PID recovery<sup>1</sup>

Technical Data	GW8000-SDT-30	GW10K-SDT-30	GW10K-SDT-EU30	GW12K-SDT-30	GW15K-SDT-30	GW17K-SDT-30	GW20K-SDT-30	GW12KLV-SDT-C30	GW17KLV-SDT-C30	GW25K-SDT-C30	GW30K-SDT-C30		
<b>Input</b>													
Max. Input Voltage (V)	1100							850		1100			
MPPT Operating Voltage Range (V)	140 ~ 1000							140 ~ 700		140 ~ 1000			
Start-up Voltage (V)	160												
Nominal Input Voltage (V)	600							420		600			
Max. Input Current per MPPT (A)	22							32 / 22		42 / 32		42 / 32	
Max. Short Circuit Current per MPPT (A)	27.5							40.0 / 27.5		52.5 / 40.0		52.5 / 27.5	
Number of MPP Trackers	2												
Number of Strings per MPPT	1							2 / 1		2		2 / 1	
<b>Output</b>													
Nominal Output Power (W)	8000	10000	10000	12000	15000	17000	20000	12000	17000	25000	30000		
Nominal Output Apparent Power (VA)	8000	10000	10000	12000	15000	17000	20000	12000	17000	25000	30000		
Max. AC Active Power (W) <sup>1</sup>	8800	11000	10000	13200	16500	18700	22000	12000	17000	27500	33000		
Max. AC Apparent Power (VA)	8800	11000	10000	13200	16500	18700	22000	12000	17000	27500	33000		
Nominal Output Voltage (V)	220 / 380, 230 / 400, 240 / 415, 3L / N / PE or 3L / PE							127 / 220, 3L / N / PE or 3L / PE		220 / 380, 230 / 400, 240 / 415, 3L / N / PE or 3L / PE			
Output Voltage Range (V)	180 ~ 280 (according to local standard)							114 ~ 139 (according to local standard)		180 ~ 280 (according to local standard)			
Nominal AC Grid Frequency (Hz)	50 / 60							60		50 / 60			
AC Grid Frequency Range (Hz)	45 ~ 55 / 55 ~ 65							59.5 ~ 60.2		45 ~ 55 / 55 ~ 65			
Max. Output Current (A) <sup>2</sup>	13.4	16.7	15.2	20.0	25.0	28.3	33.3	33.3	50.0	41.7	50.0		
Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)												
Max. Total Harmonic Distortion	<3%												
<b>Efficiency</b>													
Max. Efficiency	98.5%	98.5%	98.5%	98.5%	98.5%	98.5%	98.5%	98.2%	97.5%	98.6%	98.6%		
European Efficiency	98.0%	98.0%	98.0%	98.2%	98.2%	98.2%	98.2%	97.2%	96.9%	98.2%	98.3%		
<b>Protection</b>													
PV String Current Monitoring	Integrated												
PV Insulation Resistance Detection	Integrated												
Residual Current Monitoring	Integrated												
PV Reverse Polarity Protection	Integrated												
Anti-islanding Protection	Integrated												
AC Overcurrent Protection	Integrated												
AC Short Circuit Protection	Integrated												
AC Overvoltage Protection	Integrated												
DC Switch	Integrated												
DC Surge Protection	Type III (Type II Optional)							Type II		Type III (Type II Optional)			
AC Surge Protection	Type III (Type II Optional)												
AFCI	Optional												
Emergency Power Off	Optional												
Rapid Shutdown	Optional												
Remote Shutdown	Optional												
PID Recovery	Optional												
Power Supply at Night	Optional												
<b>General Data</b>													
Operating Temperature Range (°C)	-30 ~ +60												
Relative Humidity	0 ~ 100%												
Max. Operating Altitude (m)	4000												
Cooling Method	Natural Convection							Smart Fan Cooling					
User Interface	LED, LCD (Optional), WLAN + APP												
Communication	RS485, WiFi, LAN or 4G or Bluetooth (Optional)												
Weight (kg)	14.7	14.7	14.7	16.2	16.2	17.1	17.1	17.1	20.5	19.7	20.5		
Dimension (W x H x D mm)	491 x 392 x 210							530 x 413 x 227					
Noise Emission (dB)	<30							<45					
Topology	Non isolated												
Self-consumption at Night (W)	<1												
Ingress Protection Rating	IP66												
DC Connector	MC4 (4 ~ 6mm <sup>2</sup> )												
AC Connector	OT terminal (Max. 10mm <sup>2</sup> )			OT terminal (Max. 16mm <sup>2</sup> )				OT terminal (Max. 25mm <sup>2</sup> )					

<sup>1</sup>: For Brazil and Chile, the Max. AC Active Power (W) & Max. AC Apparent Power (VA): GW8000-SDT-30 is 8000, GW10K-SDT-30 is 10000, GW12K-SDT-30 is 12000, GW15K-SDT-30 is 15000, GW17K-SDT-30 is 17000, GW20K-SDT-30 is 20000, GW12KLV-SDT-C30 is 12000, GW17KLV-SDT-C30 is 17000, GW25K-SDT-C30 is 25000, GW30K-SDT-C30 is 30000.

GW17K-SDT-30 is 25.8, GW20K-SDT-30 is 30.3, GW12KLV-SDT-C30 is 18.2, GW17KLV-SDT-C30 is 25.8, GW25K-SDT-C30 is 37.9, GW30K-SDT-C30 is 45.5.  
<sup>2</sup>: Please visit GoodWe website for the latest certificates.

<sup>3</sup>: All pictures shown are for reference only. Actual appearance may vary.

<sup>2</sup>: For Brazil and Chile, Max. Output Current (A) and Nominal Output Current (A): GW8000-SDT-30 is 12.1, GW10K-SDT-30 is 15.2, GW12K-SDT-30 is 18.2, GW15K-SDT-30 is 22.7.

